

**"DAIKOKU LUBRICANT"**

Japanese Brand

Maker: DAITO CO., LTD.

<http://daito-japan.com/th/>

Sales Distributor: (Chachoengsao / Chonburi / Rayong)

**NISSEI USHIYAMA (THAILAND) CO., LTD.**144/79, Laemchabang City Apartment Room No. 1108,  
Moo 9, Tambol Tungsukla, Amphur Sriracha, Chonburi 20230, Thailand  
TEL : +66 (0) 33-002-262

Item	No.	Photo	Product No. & Name	Features	Applications	Packing (MOQ)
AEROSOL (D.G.)	1		<b>DKD-0702</b> <b>Less Torque</b> (Penetration Lubricant)	<ul style="list-style-type: none"> <li>- Rust Prevention.</li> <li>- Water replacement.</li> <li>- Low Viscosity and penetrative to narrow and precise part.</li> <li>- High load resistance and high lubrication by Organic Molybdenum.</li> <li>- Long-life Lubrication by Organic Molybdenum.</li> </ul>	<ul style="list-style-type: none"> <li>- Screw loosening.</li> <li>- Rust prevention.</li> <li>- Reduction of squeaking noise.</li> <li>- Tap Oil for drill.</li> <li>- Lubrication for narrow and precise space of metal contact part.</li> </ul>	420 ml / Can  24 cans / big box (12 cans x 2 small boxes)
	2		<b>DKD-0801</b> <b>Paste Spray</b>	<ul style="list-style-type: none"> <li>- "MoS2" is highly concentrated and lubricative.</li> <li>- Parts will move smoothly and make initial fitting better.</li> <li>- Prevent seizure caused by high temperature.</li> </ul>	<ul style="list-style-type: none"> <li>- Can be used for general purposes.</li> <li>- Use for assembling machines of machinery, engines and differential transmission gears.</li> <li>- Dry-type gearbox.</li> <li>- Worm gear.</li> <li>- Rack and pinion gear.</li> <li>- Anti-seizure paste for bolt and nuts.</li> </ul>	300 ml / Can  24 cans / big box (6 cans x 4 small boxes)
	3		<b>DKD-0901</b> <b>Dry Coat Spray</b>	<ul style="list-style-type: none"> <li>- It is a dry spray lubricant mixed with molybdenum disulfide (MoS2).</li> <li>- Capable of forming a quick-drying film.</li> <li>- Use with parts that cannot use oil.</li> <li>- Non-sticky property.</li> <li>- Reduction noise.</li> </ul>	<ul style="list-style-type: none"> <li>- Use with non-oiling devices that are required to be kept oil-free.</li> <li>- Heater, air conditioning unit, bolts, nuts, fan belts, Turbin blades, throttle valves.</li> <li>- To prevent brake lining noise.</li> <li>- Gear of jig in Vacuum deposition.</li> </ul>	300 ml / Can  24 cans / big box (6 cans x 4 small boxes)
FLUORINE AEROSOL SERIES (D.G.)	4		<b>DKD-9001</b> <b>Fluorine Grease Spray</b>	<ul style="list-style-type: none"> <li>- It is a grease spray lubricant.</li> <li>- The properties of fluorocarbon polymers.</li> <li>- Contains with PTFE in the fluorine oil spray.</li> <li>- Excellent lubricating properties to enhance the lubrication efficiency even further.</li> </ul>	<ul style="list-style-type: none"> <li>- Used for sliding parts and metal contacts of injection molds.</li> <li>- Slide rods, angular pins, bushings, ejector pins, pushrods, retaining parts, bearings of corrugated machines.</li> <li>- Gear sections. of the vulcanizer, filling machine, centrifugal device.</li> <li>- Bearing part of the dry vacuum pump.</li> </ul>	150 ml / Can  6 cans / box
	5		<b>DKD-9002</b> <b>Fluorine Oil Spray</b> (Medium Viscosity Type)	<ul style="list-style-type: none"> <li>- It is a fluorine oil spray.</li> <li>- The properties of fluorocarbon polymers and fluorine solvent. has excellent non-stick properties.</li> <li>- Excellent lubricating properties to enhance the lubrication efficiency even further.</li> </ul>	<ul style="list-style-type: none"> <li>- Used for lubricating tools, equipment.</li> <li>- Use to disassemble the mold.</li> <li>- To prevent rust</li> <li>- To prevent water from seeping through.</li> <li>- Improves tool durability different types of machines.</li> </ul>	150 ml / Can  6 cans / box
	6		<b>DKD-9003</b> <b>Fluorine Oil Spray</b> (High Viscosity Type)	<ul style="list-style-type: none"> <li>- Reinforced rust prevention and mold release characteristics.</li> <li>- Demonstrates an advanced mold release effect and a stain-proof.</li> <li>- Performance by forming a thin semi-dry fluorine oil film.</li> </ul>	<ul style="list-style-type: none"> <li>- Mold release for plastic injection.</li> <li>- Mold release for rubber foaming mold.</li> <li>- Dirt Prevention agent on Mold.</li> </ul>	150 ml / Can  6 cans / box
	7		<b>DKD-9004</b> <b>Fluorine Oil Spray</b> (Low Viscosity Type)	<ul style="list-style-type: none"> <li>- It is a fluorine oil spray.</li> <li>- The properties of fluorocarbon polymers and fluorine solvent. has excellent non-stick properties.</li> <li>- Excellent lubricating properties to enhance the lubrication efficiency even further.</li> </ul>	<ul style="list-style-type: none"> <li>- Suitable for electrical contact parts.</li> <li>- small resin parts.</li> <li>- Used for maintenance of air tools and switches.</li> <li>- Small Detailed Parts like a plastic gear.</li> </ul>	150 ml / Can  6 cans / box
	8		<b>DKD-007</b> <b>Brake &amp; Parts Cleaner</b>	<ul style="list-style-type: none"> <li>- High efficiency of cleaning spray.</li> <li>- It is not easy to dry quickly.</li> <li>- It can penetrate the stain with the solvent and clean remove dirty grease and oil stains very well.</li> </ul>	<ul style="list-style-type: none"> <li>- Used for maintenance and cleaning equipment in the factory and car.</li> <li>- Oil stains, dirt, dust, steel, molds and tools.</li> <li>- Used to clean brake pads, brake discs, brake cylinders, clutch discs, springs.</li> </ul>	850 ml / Can  24 cans / box

**"DAIKOKU LUBRICANT"**



Japanese Brand

Maker: DAITO CO., LTD.

<http://daito-japan.com/th/>

Sales Distributor: (Chachoengsao / Chonburi / Rayong)

**NISSEI USHIYAMA (THAILAND) CO., LTD.**144/79, Laemchabang City Apartment Room No. 1108,  
Moo 9, Tambol Tungsukla, Amphur Sriracha, Chonburi 20230, Thailand  
TEL : +66 (0) 33-002-262

Item	No.	Photo	Product No. & Name	Features	Applications	Packing (MOQ)
OIL AEROSOL (D.G.)	9		<b>DS-001</b> <b>Anti-Rust Lubricant Spray</b>	<ul style="list-style-type: none"> <li>- It is an oil spray for anti-rust and lubricant for general purposes.</li> <li>- Protects the metal surfaces.</li> <li>- Loosens rusted fittings.</li> <li>- Lubricate moving parts and inhibit corrosion.</li> <li>- Reduce friction noise and remove crude oil.</li> </ul>	<ul style="list-style-type: none"> <li>- Used for lubricating industrial tools.</li> <li>- Automotive doors and latches.</li> <li>- Anti-rust treatment for door hinge and slide lock.</li> </ul>	420 ml / Can 20 cans / box
	10		<b>DS-002</b> <b>Silicon Spray</b>	<ul style="list-style-type: none"> <li>- It is used for various lubrication.</li> <li>- Anti-rust.</li> <li>- It is non-slip and shiny.</li> <li>- Can be waterproof.</li> <li>- Resistant to the resin, rubber and virtually harmless.</li> </ul>	<ul style="list-style-type: none"> <li>- Used in mold removed for plastic and rubber injection processes.</li> <li>- Resin gear, sliding, and rolling part.</li> <li>- Sliding and hinge of doors.</li> <li>- Sliding part of wood furniture.</li> <li>- For the hold for a thread of sewing machine to prevent skitch skipping and thread broken.</li> </ul>	420 ml / Can 20 cans / box
GREASE	11		<b>DKD-003</b> <b>E-Contact Current Lube</b> (Grease for electric contact parts)	<ul style="list-style-type: none"> <li>- Use in connection points with all electrical contact of equipment types.</li> <li>- Improves electrical conductivity provide lubrication.</li> <li>- Prevents friction.</li> <li>- Increase the performance of electrical equipment for longer use.</li> </ul>	<ul style="list-style-type: none"> <li>- Applies to parts with electrical contacts - Related to technology maritime transport that requires precision.</li> <li>- Rotary switches of machines and various measuring devices.</li> <li>- Car switches in the connector.</li> <li>- Roadblock.</li> </ul>	1 kg / Can 6 cans / box
	12		<b>DKD-47</b> <b>L-Grease</b> (MoS2 Lithium Grease)	<ul style="list-style-type: none"> <li>- The multipurpose lubricating grease.</li> <li>- Made from lithium complexes mixed with molybdenum disulfide (MoS2).</li> <li>- It has better resistance to corrosion. general grease.</li> <li>- Good ability to absorb pressure and impact.</li> </ul>	<ul style="list-style-type: none"> <li>- Bearings and sliding surfaces of electric motors, blowers, conduction machines, etc.</li> <li>- Equipment machines, conveyors, etc.</li> <li>- Rolling Machine for steel works.</li> <li>- Working machines, vibratory machines.</li> </ul>	2.5 kg / Can 6 cans / box
	13		<b>DKD-150</b> <b>MP-Grease</b> (Multi-Purpose MoS2 Grease)	<ul style="list-style-type: none"> <li>- Grease composed of lithium grease mixed with MoS2.</li> <li>- Lithium-type general-purpose grease, available to be used in places needed for lubrication.</li> </ul>	<ul style="list-style-type: none"> <li>- Bearings and sliding parts for various machines.</li> <li>- Material Handling.</li> <li>- LM, Crossroller Guide.</li> <li>- Coupler of the trailer.</li> <li>- Rack and pinion gear of milling machine</li> <li>- Low-speed spindle bearing.</li> </ul>	2.5 kg / Can 6 cans / box

**"DAIKOKU LUBRICANT"**

Japanese Brand

Maker: DAITO CO., LTD.

<http://daito-japan.com/th/>

Sales Distributor: (Chachoengsao / Chonburi / Rayong)

**NISSEI USHIYAMA (THAILAND) CO., LTD.**144/79, Laemchabang City Apartment Room No. 1108,  
Moo 9, Tambol Tungsukla, Amphur Sriracha, Chonburi 20230, Thailand  
TEL : +66 (0) 33-002-262

Item	No.	Photo	Product No. & Name	Features	Applications	Packing (MOQ)
------	-----	-------	--------------------	----------	--------------	---------------

**<Application Used>****\* Please contact us for more details.\***

Mr. Shujiro NIINA (新名 周次郎)  
Director  
+66 (0) 95-753-4768  
[niina@nissei-ushiyama.co.th](mailto:niina@nissei-ushiyama.co.th)

<https://www.smri.asia/ennissei>

Ms. Suwannee Jirattanakunchai  
Sales & Marketing Manager  
+66 (0) 89-098-1331  
[suwannee@nissei-ushiyama.co.th](mailto:suwannee@nissei-ushiyama.co.th)